

# NLED924\*

IP40 downlight



### APPLICATIONS

- Sitting rooms
- Stations
- Meeting rooms
- Shopping malls


### CONSTRUCTION

- Die-cast Aluminium housing and heat sink
- Semi-transparent PMMA diffuser
- Protective plastic sleeve on spring clips
- Powder-coated finish
- Separate driver included


### TECHNICAL DETAILS

- SMD LEDs
- CRI >80
- PF >0.95
- CCT 3000K, 4000K or 5700K
- Choices of 9 wattages:
  - 7W, 700 lm
  - 12W, 960 lm
  - 15W, 1,275 lm
  - 11W, 1,200 lm
  - 20W, 1,800 lm
  - 16W, 1,600 lm
  - 22W, 2,200 lm
  - 30W, 2,700 lm
  - 34W, 3,250lm
- Rated life: 30,000 hours


Model	Color temp.	Lumens
NLED9244 7W	3000K/4000K/5700K	700 lm
NLED9244 12W	3000K/4000K/5700K	960 lm
NLED9245 15W	3000K/4000K/5700K	1,275 lm
NLED9246 11W	3000K/4000K/5700K	1,200 lm
NLED9246 20W	3000K/4000K/5700K	1,800 lm
NLED9248 16W	3000K/4000K/5700K	1,600 lm
NLED9248 22W	3000K/4000K/5700K	2,200 lm
NLED9248 30W	3000K/4000K/5700K	2,700 lm
NLED9248 34W	3000K/4000K/5700K	3,250 lm



NLED9244 12W 100°



NLED9248 20W 100°



Watts	A	B	Cutout
7W/12W	Ø114	46	Ø100
15W	Ø141	49	Ø125
11W/20W	Ø168	52	Ø150
16W/22W/30W/34W	Ø218	55	Ø200