


# FUMAGALLI LED LAMPS

MODULAR SYSTEM



Innovative **TÜV certified LED lamps** with standard E27, GX53 ,R7s, GU10 or G9 lamp holder to get a very efficient LED lighting system. Heatsink and driver are built-in the lamps. LED modules can be easily replaced without the help of a qualified technician. Available in different wattage versions and color temperature. Moreover combining in series Fumagalli GX53 lamps you get a powerful and efficient public lighting system both on classic and modern luminaries.



## BENEFITS:

- **COST SAVING:** long-life and efficient LED light sources.
- **BUILT-IN DRIVER:** quick and easy lamp replacement.
- **GREAT FLEXIBILITY:** standard lamp holder.
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.
- **SUITABLE FOR OUTDOOR USE:** driver fully protected against heat and humidity by silicone paste.
- **TÜV CERTIFIED QUALITY:** Production monitored, CE marked, LVD and EMC tested, in compliance with the European Ecodesign Directive (ERP) and with RoHS and REACH directives. CB certified.



**Power surges resistant**

- **Wide voltage range (100-240V)** to protect the driver both from voltage droop and voltage overshoot, which are quite frequent in case of outdoor installations.
- **Double 400V capacitors** and multiple resistances to withstand power surges.
- **Silicone paste** to avoid – in case of voltage swings- the vibration of the electronic components of the driver and the consequent risk of components unsoldering.



**Heat resistant - Working temperature -30°+80°C**

- **Gold wire bonding:** Chips connected by pure gold wires, which are able to withstand at the highest and lowest temperatures and at temperature fluctuations between day and night. The gold wire bonding can grant a lumens maintenance factor > 80%.
- **Silicone paste:** Thermoconductive silicone paste with metal powder inside for helping heat dissipation and avoid overheating problems and for protecting the electronic components in case of high and low temperatures.



**Humidity resistant - Weatherproof driver for a longer lifetime**

- **Silicone paste:** The driver is fully enclosed in a special silicone paste, which ensures the highest driver protection against moisture and humidity up to 90%, both unavoidable in outdoor installations.



Tested according to :  
EN 62560:2012/A1: 2015  
IEC/TR 62778:2014  
EN 62493:2015



**LVD**  
TESTED

**LVD Certificate:** Fumagalli lamps fulfil the Low Voltage Directive 2014/35/EU, therefore are CE marked and comply with safety requirements like protection against electrical shock, moisture and heat resistance, resistance to flame and ignition.

**EMC**  
TESTED

**EMC Certificate:** Fumagalli lamps meet the Electromagnetic Compatibility Directive 2014/30/EU and its amendments.

**NEW**  
**ERP**

**New ERP Attestation of conformity:** Fumagalli lamps fulfil the NEW European Ecodesign Directive EU 2019/2020, which sets stricter energy efficiency requirements, new verification tolerances and other factors such as bulb lifetime and warm-up time.

**CB**  
IECEE CB  
SCHEME

**IECEE CB Certificate:** Fumagalli lamps meet the International System for Conformity and Certification of Electrotechnical Equipment allowing direct market access in more than 50 countries all over the world.

**RoHS**  
**REACH**  
COMPLIANT

**RoHS REACH compliant:** Fumagalli lamps fulfil the RoHS (Restriction of Hazardous Substances) directive 2011/65/EU and its amendments and the REACH regulation (EC) No. 1907/2006, regarding the concentration of Very High Concern Substances (SVHC).



GARDEN REVIVAL  
GARDEN CLASSIC  
BOLLARD  
UP&DOWN  
DOWNLIGHT  
IN-GROUND  
BRICKLIGHT  
FLOODLIGHT  
BULKHEAD  
SOLAR  
URBAN CLASSIC  
URBAN REVIVAL  
URBAN MODERN  
POST  
LAMPS

# GX53 LED Ø75mm

TÜV- CB CERTIFIED LED MODULES



## INDOOR & OUTDOOR USE

-30 +80 °C      90% HUMIDITY

VOLTAGE SURGE RESISTANT



### PCB AND CONNECTION RING

- Special connection ring to avoid the PCB deformation under high temperatures and to keep the PCB adhering to the heatsink.



### LENS

- Frosted color lens reducing dazzle.
- Made of UV stabilized resin material to avoid yellowing process.
- Very compact and **slim design** for a better light distribution and for improving the light efficiency.



### GOLD WIRE BONDING

- LED chips connected by pure **gold wires** able to withstand at the highest and lowest temperatures and granting a **lumens maintenance factor > 80%**.
- SMD 3528 LED.



### DRIVER 100-240V

- IC isolated driver technology.
- Wide voltage range: **100-240V** +/- 10% tolerance to protect the driver both from voltage droop and voltage overshoot.
- High quality capacitors and multiple resistances able to withstand power surges.




### GX53 LAMPHOLDER


- Quick and easy lamp replacement and version upgrade.
- Made of PBT material resisting up to 180° and 250V.
- VDE certified.






### CCT SETTABLE

- Switch settable in three different positions, to select the desired Kelvin temperature (3000K, 4000K, 6500K) and get a customized ambiance.
- 3000K, 4000K and 6500K led chips on 3 separate circuits to grant SDCM < 6.





GX53 LED Ø75mm- CCT SETTABLE																										
	<table border="1"> <tr> <td>POWER</td> <td colspan="2" style="text-align: center;"><b>3 W</b></td> </tr> <tr> <td rowspan="3">LUMINOUS FLUX (Φ TOTAL)</td> <td style="background-color: #f1c40f;">3000 K</td> <td>405 lm</td> </tr> <tr> <td>4000 K</td> <td>410 lm</td> </tr> <tr> <td style="background-color: #3498db;">6500 K</td> <td>410 lm</td> </tr> </table>	POWER	<b>3 W</b>		LUMINOUS FLUX (Φ TOTAL)	3000 K	405 lm	4000 K	410 lm	6500 K	410 lm															
	POWER	<b>3 W</b>																								
	LUMINOUS FLUX (Φ TOTAL)	3000 K	405 lm																							
4000 K		410 lm																								
6500 K		410 lm																								
<p>SIZE &amp; SOCKET</p> 																										
<div style="display: flex; justify-content: space-between;"> <div style="width: 20%;"> <p><b>CCT SETTABLE</b></p> <p>3000 K 4000 K 6500 K</p> <p>SDCM &lt;6</p> </div> <div style="width: 20%;"> <p><b>ENERGY</b></p> <p>FUMAGALLI SRL H.LED.G53.CCT(VQ)</p>  <p>3 kWh/1000h</p> <p>COMPLY WITH: EU 2019/2015 EU 2019/2020</p> </div> <div style="width: 20%;"> <p><b>TUV</b></p> <p>CE LVD CB EMC ERP</p> <p><b>IECEE</b></p> <p>IECEE CB CERTIFICATE: SG PSB-LE-03887</p> </div> <div style="width: 35%;"> <table border="1"> <tr><td>LUMINOUS FLUX (Φ USE 120°)</td><td>335 lm</td></tr> <tr><td>VOLTAGE</td><td>100-240 V</td></tr> <tr><td>FREQUENCY</td><td>50/60 Hz</td></tr> <tr><td>PSTLM (NO FLICKER)</td><td>&lt; 1</td></tr> <tr><td>SVM</td><td>0,4</td></tr> <tr><td>CRI</td><td>&gt; 80</td></tr> <tr><td>SDCM</td><td>&lt;6</td></tr> <tr><td>BEAM ANGLE</td><td>112°</td></tr> <tr><td>SWITCHING CYCLE</td><td>&gt; 30.000</td></tr> <tr><td>WARM UP TIME</td><td>0s</td></tr> <tr><td>LIFETIME</td><td>25.000 h</td></tr> <tr><td>EFFICIENCY CLASS</td><td>E</td></tr> <tr><td>REF. CODE</td><td>H.LED.G53.CCT</td></tr> </table> </div> </div>	LUMINOUS FLUX (Φ USE 120°)	335 lm	VOLTAGE	100-240 V	FREQUENCY	50/60 Hz	PSTLM (NO FLICKER)	< 1	SVM	0,4	CRI	> 80	SDCM	<6	BEAM ANGLE	112°	SWITCHING CYCLE	> 30.000	WARM UP TIME	0s	LIFETIME	25.000 h	EFFICIENCY CLASS	E	REF. CODE	H.LED.G53.CCT
LUMINOUS FLUX (Φ USE 120°)	335 lm																									
VOLTAGE	100-240 V																									
FREQUENCY	50/60 Hz																									
PSTLM (NO FLICKER)	< 1																									
SVM	0,4																									
CRI	> 80																									
SDCM	<6																									
BEAM ANGLE	112°																									
SWITCHING CYCLE	> 30.000																									
WARM UP TIME	0s																									
LIFETIME	25.000 h																									
EFFICIENCY CLASS	E																									
REF. CODE	H.LED.G53.CCT																									